

Page 1 of 6

Doc. No. 913-0003-001 Revision 03

Preparation Date: August 27, 2013

Material Safety Data Sheets (MSDS) are a sub-requirement of the Occupational Safety and Health Administration (OSHA) Hazard Communication Standard, 29 CFR Subpart 1910.1200. This Hazard Communication Standard does not apply to various subcategories including anything defined by OSHA as an "article". OSHA has defined "article" as a manufactured item other than a fluid article; (i) which is formed to a specific shape or design during manufacture; (ii) which has end use function(s) dependent in whole or in part upon its shape or design during end use; and (iii) which under normal conditions of use does not release more than very small quantities, e.g. minute or trace amounts of hazardous chemical, and does not pose a physical hazard or health risk to employees. Boston-Power batteries are defined as "articles" and are exempt from requirements of the Hazard Communication Standard; hence an MSDS is not a requirement. This datasheet is provided as a service to our customers and vendors.

# **Section 1: Product Information**

Product Identification: Lithium-Ion Rechargeable Cell

Cell Trade name: Sonata® 5300 and Swing® 5300 (formerly known as Sonata®Gen2 and

Swing®Gen2)

Chemical System: Lithium ion

#### Manufacturer:

US Operations	China Operations	
Boston-Power, Inc.	Boston-Power Battery (Jiangsu) Co., Ltd.	
2200 West Park Drive, Suite 320 3F Building E, No. 168 Wushen Road,		
Westborough, MA 01581-3961,	Liyang Economic Development Zone,	
USA	Liyang 213300 Jiangsu, China	
Phone: +1.508.366.0885	Phone: +86.519. 8098.7688	
www.boston-power.com	www.boston-power.com.cn	

# Section 2: Composition/Information on Ingredients

The chemical ingredients are contained in a sealed case designed to withstand temperatures and pressures encountered during normal use. The cell should not be opened, disassembled, crushed, burned, or exposed to high temperatures because exposure to the following materials could be harmful under some circumstances. The following information is provided for the user's information only.



Page 2 of 6

Doc. No. 913-0003-001	Revision	03
-----------------------	----------	----

Chemical Ingredients	Weight %	CAS Number
Complex Lithium Nickel Oxide. Similar chemical properties to Lithium Nickel Cobalt Oxide	20-50	Similar chemical properties to 113066-89-0
Polyvinylidene Fluoride (PVDF)	<5	24937-79-9
Graphite	10-30	7782-42-5
Organic Electrolyte Solvent – Proprietary Similar chemical properties to Ethylene carbonate	10-20	Similar chemical properties to 96-49-1
Electrolyte Salt – Lithium hexafluorophosphate	1-3	21324-40-3
Aluminum, Nickel, Copper and inert materials	Remainder	N/A

# **Section 3: Health Hazard Data Emergency Overview**

Cell may explode in a fire, which could release gases or solvents irritating to the skin and eyes. Use extinguishing media suitable for materials burning in fire.

# **Primary Routes of Entry – in the event that internal cell contents are released:**

Skin Contact	Yes
Skin Absorption	Yes
Eye Contact	Yes
Inhalation	Yes
Ingestion	Yes

## **Symptoms of exposure**

The contents of the battery are contained within a sealed can and under routine handling and use and will have no effect.

#### Reported as carcinogen

Not applicable

# **Section 4: First Aid Measures**

IF EXPOSURE TO INTERNAL MATERIALS WITHIN CELL DUE TO DAMAGED OUTER CASING, THE FOLLOWING ACTIONS ARE RECOMMENDED;

#### Inhalation

Leave area immediately and seek medical attention.

# Eye contact

Check for and remove any contact lenses. Rinse eyes with water or normal saline 15 minutes and seek medical attention.

#### **Skin contact**

Remove contaminated clothes and shoes. Wash area thoroughly with soap and water and seek medical attention.

#### Ingestion

Wash mouth with water. Drink milk/water and induce vomiting; seek medical attention.



Page 3 of 6

Doc. No. 913-0003-001 Revision 03

# **Section 5: Fire Fighting Measures**

#### **General Hazard**

Cell is not flammable. Combustion products include, but are not limited to hydrogen fluoride, carbon monoxide and carbon dioxide.

#### **Extinguishing Media**

Use extinguishing media suitable for the materials that are burning.

### **Special Firefighting Instructions**

If possible, remove cell from fire fighting area. If heated above 150°C, cell may explode.

## **Firefighting Equipment**

Use NIOSH/MSHA approved full-face self-contained breathing apparatus (SCBA) with full protective gear.

#### Section 6 - Accidental Release Measures

**On land:** Place material into suitable containers and call local fire/police department.

In water: If possible, remove from water and call local fire/police department.

# Section 7 - Handling and Storage

## Handling

No special protective clothing required for handling an individual cell.

#### Storage

Store in a cool, dry place.

## **Section 8 - Exposure Controls / Personal Protection**

#### **Engineering Controls**

Keep away from heat and open flame. Store in a cool, dry place.

#### **Personal Protection**

Respirator not required during normal operations. SCBA required in the event of a fire.

# Eye/face protection

Not required beyond safety practices of employer.

#### **Gloves**

Not required for handling of cells.

#### Foot protection

Steel toed shoes recommended for large container handling.



Page 4 of 6

Doc. No. 913-0003-001 Revision 03

**Section 9 - Physical and Chemical Properties** 

State	Solid
Odor	N/A
рН	N/A
Vapor pressure	N/A
Vapor density	N/A
Boiling point	N/A
Solubility in water	Insoluble
Specific gravity	N/A
Density	N/A

# **Section 10: Stability and Reactivity**

#### Reactivity

None

# **Incompatibilities**

None during normal operation. Avoid exposure to heat, open flame and corrosives.

## **Hazardous Decomposition Products**

None during normal operating conditions. If cells are opened, hydrogen fluoride and carbon monoxide may be released.

#### **Conditions to Avoid**

Avoid exposure to heat and open flame. Do not puncture, crush or incinerate.

## **Section 11: Toxicological Information**

This product does not elicit toxicological properties during routine handling and use.

Sensitization	Teratogenicity	Reproductive Toxicity	Acute Toxicity
NO	NO	NO	NO

If cells are opened through misuse or damage, discard immediately according to all federal, state and local regulations. Internal components of cell are irritants and sensitizers.

# **Section 12: Ecological Information**

Some materials within the cell are bioaccumulative. Under normal conditions, these materials are contained and pose no risk to persons or the surrounding environment.

## **Section 13: Disposal Considerations**

California regulated debris RCRA Waste Code: Non-regulated - Dispose of according to all federal, state and local regulations.



Page 5 of 6

Doc. No. 913-0003-001 Revision 03

# **Section 14: Transport Information**

Regulated under U.S. DOT HMR, 49 CFR parts 171-180 Boston-Power's Sonata<sup>®</sup> 5300 and Swing<sup>®</sup> 5300 lithium-ion cells are categorized as medium secondary cells which comply with the testing requirements defined by section 38.3 of the UN Manual of Tests and Criteria. According to the authority and with reference to the packaging defined in the following transportation regulations:

- UN Recommendations on the Transportation of Dangerous Goods Model Regulations
  - Product has been found to conform to section 38.3 of the UN Manual of Tests and Criteria by Motorola Product Test Services MPTS #3594 (Sonata) and 3599 (Swing)
- International Civil Aviation Organization (ICAO) Technical Instructions
- International Air Transport Association (IATA) Dangerous Goods Regulations
  - Cell Wh rating = 19.3Wh (requirement < 20Wh) and therefore falls under UN 3480 Packing Instruction 965:
    - If quantity is 8 cells or less they can be declared and shipped as excepted non-dangerous good under Section II.
    - If quantity is greater than 8 cells they must declared as Class 9 dangerous good under Section IB.
  - This product incorporates a safety venting device that will preclude a violent rupture under conditions normally incident to transportation.
  - Cells are packaged in strong outer packaging conforms to 5.0.2.4, 5.0.2.6.1, 5.0.2.12.1
  - Inner packaging completely encloses the cell to prevent short circuits including protection against contact with conductive materials with the same packaging.
  - The cell packaging conforms to 1.2m drop test validated by the Shanghai Research Institute of Chemical Industry Testing Centre, report #1112090105.
  - Each package is labeled with lithium ion battery handling labels and 24 hour emergency contact information and declared in shipping documentation as: Lithium ion batteries
  - The MAXIMUM gross weight per package is 10Kg
- International Maritime Dangerous Goods (IMDG) Code
  - Cell Wh rating = 19.3Wh (requirement < 20Wh) and therefore falls under Special Provision 188 and can be shipped as excepted non-dangerous good
- Europe, road transportation
  - Cell Wh rating = 19.3Wh (requirement < 20Wh) and therefore falls under ADR Special Provision 188 and can be shipped as excepted non-dangerous good
- China SN/T 0370.1-2009 and MH/T 1020-2009
  - Product has been found to conform to the Safe Transportation of Chemical Goods by the Shanghai Research Institute of Chemical Industry Testing Centre, report #2112090630 (AIR ONLY)



Page 6 of 6

Doc. No. 913-0003-001 Revision 03

For surface and vessel shipments within the United States the transportation of Boston-Power's Sonata® 5300 and Swing® 5300 lithium-ion cells must be shipped under UN3090 as a fully regulated Class 9 dangerous good:

- U.S. Department of Transportation Hazardous Materials Regulations (HMR): Surface, Vessel
  - $_{\odot}$  Cell ELC (Effective Lithium Content) = 1.59g (>1.50g) and is classified as a medium cell and must be shipped as Class 9
  - o Packaging Group II packaging per 49 CFR 173.185, same as IATA above
  - o All shipping documentation must declare shipment as Class 9
  - Multimodal shipments that include air mode fall under the IATA rules above

Section 15: Regulatory Information
------------------------------------

OSHA hazard	communication	standard (29 C	CFR 1910.1200)
	Hazardous		Non-hazardous

#### **Section 16: Other Information**

This product is designed for use by persons trained in the handling and use of lithium-ion cells and is not intended for individual sale. Under normal use this product poses no exposure risk. In the event that internal contents of lithium-ion cell are released due to damage or severe heating, then precautions should be taken to avoid any exposure and properly trained safety personnel should be contacted for clean up and disposal.

Boston-Power, Inc. believes the information in this publication is correct, however, the information is subject to change without notice.

© Boston-Power, Inc., 2012, 2013. All rights reserved.

No portion of this material may be copied or reproduced, in any manner, without the express written consent of Boston-Power. "Boston-Power®", "Sonata®" and "Swing®" are registered trademarks of Boston-Power, Inc., which retains sole rights to their use.